

DOWNFORCE – UNI FILTER

INSTALLATION AND USER'S INSTRUCTIONS

Thank you for purchasing the Uni Filter from Downforce.

Before beginning any removal or installation, please take time to thoroughly read through the instructions. The filter will not affect the operation of your smog equipment on your car. This instruction is available for download online at <http://www.downforce.biz/manuals/>

- There are several WARNING sections in the installation. Always read and follow the instruction to prevent injuries, accidents, and possible damage to the vehicle.
- Do not modify the Air Filter.
- Do not install the Air Filter in any way other than described in the following instructions.
- If you have any questions about the use of the Air Filter, ask Downforce about any concerns.
- Downforce and its dealers are not responsible for injuries, accidents, and damage to persons and property that arise from the use of this product.
- This product is for off road use only.

PART NAME	UNI FILTER
PART NUMBER	DF-50075
VEHICLE	ACURA NSX 1991-2005

1 Requirements



You will need the factory air box installed to properly use this product. This air filter is specifically made to fit inside the Acura NSX airbox cleaner.

Part Number	Description	Retail Price
17210-PR7-A50	Cover Air Cleaner	\$136.29
17241-PR7-A01	Housing Air Cleaner	\$166.87

2 Tools and Equipments Needed



Philips head #2
Screwdriver


3 Air Filter Replacement

LOOSEN THE CLAMP HERE



Loosen Rubber Air Coupler

Use the screwdriver to loose the clamp that is directly connected on the airbox cleaner. The accordion type hose allows you to pull the hose off easily. You may also loose any rubber hoses that are connected to the box for additional clearance. Once the accordion hose is off you will now have a good leverage point to pull the cover off when it comes time to remove it.



Once you have removed the screws take out the factory air filter element and do any necessary cleaning to the airbox. Place the Uni Filter into the air box and Replace the top cover and tighten all screws and clamps.

Note: Make sure that the drainage hole on the base of the airbox is free from obstructions.

4 Maintenance

The Comptech Uni-Filter will last for a lifetime if taken care of properly, it comes pre-oiled in the package. It is important that once the filter is soiled, that you clean the filter and re-oil. Cleaning the air filter can be done with any off the shelf or household degreaser such as Oil Eater, 409, Simple Green, Dawn etc. The dirtier the air filter becomes the less efficient it will be filtering the air. Foamed oil filters are the best performing type of filter media on the market for the automotive industry. It has the highest load capacity and greatest flow rate and filtering ability when compared the paper and oiled cotton filters. This filter is designed to work with oil and without the oil there is absolutely nothing catching the micron-sized dirt particles picked up from the outside environment. It is best to use special air filter oil from AMSOIL or Uni-Filter. Check on the filter every 7,000 miles (or 2 oil changes). If you see any dirt or debris on the back side of the filter then it is time to clean the filter. Additional air filter oil is available from Downforce direct.

Part Number	Description	Price
DF-50076	UNI FILTER SERVICE KIT	\$15.00
DF-50077	UNI FILTER OIL 5.5 OZ SPRAY	\$5.95
DF-50078	UNI FILTER OIL 16 OZ BOTTLE	\$5.95